

SPESIFIKASI

NO	PRODUK	SPESIFIKASI	MERK	TYPE	NEGARA ASAL
1	Patient Monitor	Features: - Adult, Pediatric, and Neonatal Application - Innovative One-Level-Menu - simple & easy to use - Various Parameters including ECG/RESP, SpO2, NIBP, TEMP, Pulse Rate - Maximum 72 hours Graphic and Tabular Trends of all Parameters - Built-in Battery - Arrhythmia Analysis, ST Calculation, Pace Analysis - Anti-ESU, Anti-Defibrillator - Standard Network Interface - Connection to Central Monitor System (CMS)	Heyer	Scalis 12" + Printer	Germany
		Spesification :			
		Display : 12" color TFT display			
		Waveforms : up to 12 waveforms			
		ECG			
		Lead mode : I, II, III, AVR, AVL, AVF, V			
		Gain : x0.25, x0.5, x1, x2			
		Heart Rate : 15 - 300 bpm (Adult)			
		: 15 - 350 bpm (Neonatal)			
		: Resolution:1 bpm			
		: Accuracy:1%			
		ST measurement : Range: -2.0 - +2.0 mV			
		: Accuracy: ±10%			
		Pacemaker : Yes			
		Sweep Speed : 12.5 mm/s, 25 mm/s, 50 mm/s			
		Bandwidth : Diagnostic: 0.05 - 130 Hz			
		: Monitor: 0.5 - 40 Hz			
		: Surgery: 1 - 20 Hz			
		SpO2			
		Measure range : 0 - 100%			
		: Resolution: 1%			

			: Accuracy: 2% (70-100%)			
		Pulse Rate	: 20 - 250 bpm			
			: Resolution: 1 bpm			
			: Accuracy: ± 3 bpm			
		RESP				
		Measure range	: 0 - 150 bpm			
		Resolution	: 1 bpm			
		Accuracy	: $\pm 2\%$			
		TEMP				
		Channel	2			
		Measure range	: 0 - 50°C			
		Resolution	: 0.1°C			
		Accuracy	: $\pm 0.1^\circ\text{C}$			
		NIBP				
		Method	: Oscillometry			
		Work Mode	: Manual, Automatic, Continuous			
		Unit	: mmHg, kPa			
		Measure range				
			Adult : SYS: 40 - 280 mmHg			
			: DIA: 10 - 225 mmHg			
			: MEAN: 20 - 240 mmHg			
			Pediatric : SYS: 40 - 220 mmHg			
			: DIA: 10 - 160 mmHg			
			: MEAN: 20 - 170 mmHg			
			Neonatal : SYS: 40 - 135 mmHg			
			: DIA: 10 - 100 mmHg			
			: MEAN: 20 - 110 mmHg			
			: Resolution: 1 mmHg			
			: Accuracy: ± 5 mmHg			
		Recorder				
		Model	: Thermal Printer			
		Printing Speed	: 12.5, 25, 50 mm/sec			

		General :			
		Power Supply	: 100V~240 V, 50Hz/60 Hz		
		Pmax	: 90 VA		
		Fuse	: T1.5AL 250V		
		Battery	: 2.3 Ah 12V rechargeable battery		
		Accessories :			
		NIBP Cuff With extention tube	: 1 pc		
		ECG cable 5 Lead	: 1 pc		
		ECG cable 3 Lead	: 1 pc		
		SpO2 Sensor	: 1 pc		
		Temp Sensor	: 1 pc		
		Printer paper	: 1 pc		