

Emergency Transport Ventilator

Model VA-3L

- For emergency, transportation and short-time treatment uses
- Ventilation modes: A/C, SIGN, SIMV, SPONT, MANUAL
- Waveform display and multi-parameter monitoring
- Flexible power supply: A/C, ambulance D/C, rechargeable built-in battery
- Back-up apnea ventilation

Specifications:

Tidal volume	: 0~1500 ml
Breath rate	: 4~99 bpm
IE ratio	: 1:0.5, 1:1, 1:1.5, 1:2, 1:3, 1:4
Trigger sensitivity	: -20~0 cm H ₂ O
High pressure	: 0~80 cm H ₂ O
Low pressure	: 0~20 cm H ₂ O
FiO ₂	: 48%~100%
Battery operation	: > 4h
Cylinder	: 3 L, aluminium
Power supply	: ~220V, 50 Hz; ~110V, 60 Hz; 12 V(D/C)
Dimensions	: 500x190x400mm



Distributed by:

PT. Megah Alkesindo

Kompleks Ruko Rawa Bambu
Jl. Rawa Bambu Raya No. 15 G-H
Pasar Minggu Jakarta Selatan 12520 Indonesia
Phone : +62 21 788 44990
Email : info@megahalkesindo.com