

SPESIFIKASI

NO	PRODUK	SPESIFIKASI	MERK	TYPE	NEGARA ASAL
1	Ventilator Transport VA-3L	Features : - Usefull for emergency situation, transportation and short time treatment - Ventilation mode : A/C, SIGN, SIMV, SPONT, MANUAL - Waveform display and multiparameter monitoring - Flexible power suply : A/C, ambulance D/C, rechargable built in battery - Back up apnea ventilation Technical spesification : - Tidal volume : 0-1500 ml - Breath rate : 4-99 bpm - IE ratio : 1:0.5, 1:1, 1:1.5, 1:2, 1:3, 1:4 - Trigger sensitivity : -20~0 cm H2O - High pressure : 0-80 cm H2O - Low pressure : 0-20 cm H2O - FiO2 : 48%~100% - Battery operation : > 4 hours - Cylinder : 3 L aluminium - Power suply : ~220V, 50 Hz, ~110V, 60 Hz, 12V (D/C) Accessories : - PAW Hose Silicone : 1 pc - Respiration Valve with 3 Outlets : 1 pc - Test Ballon 1 L : 1 pc - Silicone Respiration Hose : 1 pc - Mask Holder : 1 pc - Adult Face Mask : 1 pc - Peep valve : 1 pc - Peep valve connector : 1 pc	Uzumcu	VA-3L	Turkey - Europe