

SPECIFICATION

NO	PRODUCT NAME	SPECIFICATION	BRAND	TYPE	ORIGIN COUNTRY
1	MMM Selectomat PL 6618	Standard equipment	Munchener	PL 6618	Germany
		• Suitable for all kind of sterilization material			
		• Easy installation and operation			
		• Industrial PLC control system by B&R			
		• Independent from media supply on site			
		• Small footprint			
		• Automatic Sliding door Left or right door opening			
		• Water saving vacuum pump system			
		• Machine width of 995 mm			
		• Smart HMI 10" / 16:9			
		• LED chamber light			
		Sterilization programs			
		• Universal 134°C			
		• Universal SD 134°C			
		• Plastics 121°C			
		• B & D test 134°C			
		• Vacuum test			
		• Passing through			
		• Creutzfeldt-Jakob program 134°C			
		• Preheating			
		• Free programs			
		CHAMBER			
		• Dimension approx. 702 x 652 x 1940 mm			
		• Capacity approx. 883 L			
		• Provided with 2 vertical sliding doors			
		SYSTEM SUPPORT			
		• Silenced air compressor			
		• Vacuum process with liquid ring vacuum pump			
		• Pressure recording sensor			
		• Air leakage detection system			
		ELECTRICITY			
		380V, 50/60 Hz, approx. 56 kW			
		ACCESSORIES			
		• Loading cart (1 set)			
		• Loading and/or unloading trolleys (1 set)			