

SPECIFICATION

NO	PRODUCT NAME	SPECIFICATION	BRAND	TYPE	ORIGIN COUNTRY
1	MMM Selectomat SL 666	<p>Standard equipment</p> <ul style="list-style-type: none"> • Integrated electric steam generator with automatic scouring device • Water saving vacuum pump • Special chamber jacket for improved chamber preheating and reduction of demineralized water consumption • Ceramic bead blasted inner chamber walls • Chip card reader • Touch screen 8.2" • Display of remaining cycle time • Low-noise thermo-printer for batch documentation <p>Sterilization programs</p> <p>Standard:</p> <ul style="list-style-type: none"> - Preheating 134° C - Universal 134° C - Universal Container 134° C - Rubber 121° C - Tools fast - Free programs <p>Test programs:</p> <ul style="list-style-type: none"> - BD test 134° C - Vacuum test - Service <p>CHAMBER</p> <ul style="list-style-type: none"> • Dimension approx. 700 x 650 x 690 mm • Capacity approx. 314 L • Provided with 2 vertical sliding doors <p>SYSTEM SUPPORT</p> <ul style="list-style-type: none"> • Silenced air compressor • Vacuum process with liquid ring vacuum pump • Pressure recording sensor • Air leakage detection system <p>ELECTRICITY</p> <p>380V, 50/60 Hz, approx. 38 kW</p> <p>ACCESSORIES</p> <ul style="list-style-type: none"> • Loading cart (1 pc) • Loading and/or unloading trolleys (1 set) 	Muchener	SP SL 666 FPED	Czech Republic