## **SPECIFICATION**

NO	PRODUCT NAME	SPECIFICATION	BRAND	TYPE	ORIGIN COUNTRY
1	MMM Selectomat PL 666	Standard equipment	Munchener	PL 666	Germany
		Suitable for all kind of sterilization material			
		Easy installation and operation			
		Industrial PLC control system by B&R			
		Independent from media supply on site			
		Small footprint			
		Automatic Sliding door Left or right door opening			
		Water saving vacuum pump system			
		Machine width of 995 mm			
		• Smart HMI 10" / 16:9			
		LED chamber light			
		Sterilization programs			
		Universal 134°C			
		Universal SD 134°C			
		Plastics 121°C			
		• B & D test 134°C			
		Vacuum test			
		Passing through			
		Creutzfeldt-Jakob program 134°C			
		Preheating			
		Free programs			
		CHAMBER			
		Dimension approx. 702 x 652 x 690 mm			
		Capacity approx. 314 L			
		Provided with 2 vertical sliding doors			
		SYESTEM SUPPORT			
		Silenced air compressor			
		Vacuum process with liquid ring vacuum pump			
		Pressure recording sensor			
		Air leakage detection system			
		ELECTRICITY			
		380V, 50/60 Hz, approx. 24 kW			
		ACCESSORIES			
		Loading cart (1 pc)			
		Loading and/or unloading trolleys (1 set)			
		3			