


Height rods KERN MSF



6 KERN MSF 200

Mechanical height rod

Features

- Measuring range 60–205 cm (23½–78¾ inch);

increments of 1 mm (1/16 inch)

- **7** Readability on scale with moveable, foldable stop or mounting on KERN scales MPS-PM (page 14), MPB-P (page 16) MTS-M (page 38) or **8** wall-mounted
- Sturdy aluminum profile
- Overall dimensions max.
W×D×H 60×330×1630 mm
- Net weight approx. 0,7 kg

STANDARD



Pictograms

 Adjusting program CAL: For quick setting up of the balance's accuracy. External adjusting weight required.	 Hold function: When the weighing conditions are unstable, a stable weight is calculated as an average value.	 Binocular Microscope: For the inspection with both eyes
 Data interface RS-232: To connect the balance to a printer, PC or network.	 Protection against dust and water splashes IPxx: The type of protection is shown in the pictogram.	 Trinocular Microscope: For the inspection with both eyes and the additional option for the connection of a camera
 RS-485 data interface: To connect the balance to a printer, PC or other peripherals. Suitable for data transfer over large distances. Network in bus topology is possible	 Stainless steel: The balance is protected against corrosion.	 Abbe Condenser: With high numerical aperture for the concentration and the focusing of light.
 Bluetooth* data interface: To transfer data from the balance to a printer, PC or other peripherals.	 Suspended weighing: Load support with hook on the underside of the balance.	 Halogen illumination: For pictures bright and rich in contrast.
 Control outputs (optocoupler, digital I/O): To connect relays, signal lamps, valves, etc.	 Battery operation: Ready for battery operation. The battery type is specified for each device.	 LED illumination: Cold, energy saving and especially long-life illumination.
 Statistics: using the saved values, the device calculates statistical data, such as average value, standard deviation etc.	 Rechargeable battery pack: Rechargeable set.	 Fluorescence illumination for compound microscopes: With 100 W mercury lamp and filter.
 PC Software: to transfer the measurements from the device to a PC.	 Battery operation rechargeable: Prepared for a rechargeable battery operation	 Fluorescence illumination for compound microscopes: With 3 W LED illumination and filter.
 GLP/ISO-Protokoll: With date and time. Only with KERN printers.	 Universal mains adapter: with universal input and optional input socket adapters for A) EU, CH B) EU, CH, GB, USA	 Phase contrast unit: For a higher contrast.
 Piece counting: Reference quantities selectable. Display can be switched from piece to weight.	 Mains adapter: 230V/50Hz in standard version for EU. On request GB, AUS or USA version available.	 Darkfield condenser/unit: For a higher contrast due to indirect illumination
 Totalising level A: The weights of similar items can be added together and the total can be printed out.	 Power supply: Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, AUS or USA on request.	 Polarising unit: To polarise the light.
 Weighing units: Can be switched to e.g. nonmetric units at the touch of a key. Please refer to website for more details.	 Weighing principle: Strain gauges Electrical resistor on an elastic deforming body.	 Infinity system: Infinity corrected optical system.
 Weighing with tolerance range: (Check weighing) Upper and lower limiting can be programmed individually, e.g. for sorting and dosing. The process is supported by an audible or visual signal, see the relevant model	 Peak hold function: capturing a peak value within a measuring process.	 Verification possible: The time required for verification is specified in the pictogram.
 Hold function: When patients do not stand, sit or lie completely still, a stable weight is calculated using an average weight.	 Push and Pull: the measuring device can capture tension and compression forces.	 Package shipment: The time required for internal shipping preparations is shown in days in the pictogram.
	 Integrated scale: In the eyepiece.	 Pallet shipment: The time required for internal shipping preparations is shown in days in the pictogram.
	 360° rotatable microscope head	
	 Monocular Microscope: For the inspection with one eye.	

*The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by KERN & SOHN GmbH is under license. Other trademarks and trade names are those of their respective owners.

Your KERN specialist dealer