

Cold Rooms for Body

STRUCTURAL CHARACTERISTICS

BOX CONSTRUCTION

The box is composed of modular sandwich-type panels comprising two metal plates with a layer of rigid polyurethane foam injected between them for thermal insulation. Panel thickness: 80 mm

STANDARD EQUIPMENT

- Refrigeration unit illumination by microswitch positioned on the doors with automatic system switch-off.
- Digital read-out electronic control panel.
- Temperature variation and malfunction alarm.
- Fluid discharge unit positioned on the floor.
- Antic condensate electric resistance on the doors (for low-temperature units).



 2480
  1090
  2260 mm

Type: CEACA13

3 bodies cold rooms & 3 front doors

Technical Data of CEACA13:

- A - Operating temperature: 0 ° C*
- B - Temperature range: -5 ° C / +5 ° C*
- C - Power consumption: 1.1 kW*
- D - Power supply voltage: 230V / 1/50 Hz*
- E - Cooling capacity: 1600W 0 ° C / +35 ° C*

Distributed by:

PT. Megah Alkesindo

Kompleks Ruko Rawa Bambu
 Jl. Rawa Bambu Raya No. 15 G-H
 Pasar Minggu Jakarta Selatan 12520 Indonesia
 Phone : +62 21 788 44990 (Hunting)
 Service : +62 21 2899 4111
 Fax : +62 21 788 47144
 Email : info@megahalkesindo.com