

Cold Rooms for Body

STRUCTURAL CHARACTERISTICS

BOX CONSTRUCTION

The box is composed of modular sandwich-type panels comprising two metal plates with a layer of rigid polyurethane foam injected between them for thermal insulation. Panel thickness: 80 mm

STANDARD EQUIPMENT

- Refrigeration unit illumination by microswitch positioned on the doors with automatic system switch-off.
- Digital read-out electronic control panel.
- Temperature variation and malfunction alarm.
- Fluid discharge unit positioned on the floor.
- Antic condensate electric resistance on the doors (for low-temperature units).



 2080
  2040
  2260 mm

Type: CEACA22

4 bodies cold rooms & 4 front doors

Technical Data of CEACA22:

- A - Operating temperature: -20 ° C
- B - Temperature range: -10 ° C / -20 ° C
- C - Power consumption: 1,3 kW
- D - Power supply voltage: 230V & 380V/ 50 Hz
- E - Cooling capacity: 1300W -20 ° C / +35 ° C

Distributed by:

PT. Megah Alkesindo

Kompleks Ruko Rawa Bambu
 Jl. Rawa Bambu Raya No. 15 G-H
 Pasar Minggu Jakarta Selatan 12520 Indonesia
 Phone : +62 21 788 44990 (Hunting)
 Service : +62 21 2899 4111
 Fax : +62 21 788 47144
 Email : info@megahalkesindo.com