

SPESIFIKASI EK-410

NO	PRODUK	SPESIFIKASI	MERK	TYPE	NEGARA ASAL
1	Electrosurgical Unit 400 Watt	Features : - Monopolar - Bipolar Operation - Controlled Cutting Procedures - Twin Controlled Coagulative Prosedures - Wide Bipolar Features - Surgeon And Patient Safety - Personalized Procedures - Extention Driver And Interlock Signals - Automatic Self Diagnosis - Vessel Sealing Features Specification : MONOPOLAR - Maximum output power pure CUT : 400 W - 300 Ω - Maximum output power cut- coag CUT 80% : 300 W - 300 Ω - Maximum output power cut- coag CUT 60% : 250 W - 300 Ω - Maximum output power cut- coag CUT 40% : 200 W - 300 Ω - Maximum output power cut ENHANCED : 250 W - 500 Ω - Maximum output power cut- coag BLEND : 250 W - 300 Ω - Maximum output power coag SPEEDY : 120 W - 500 Ω - Maximum output power coag DEEP : 120 W - 200 Ω - Maximum output power coag SPRAY : 100 W - 2000 Ω - Maximum output power coag SPRAY ARGON : 100 W - 2000 Ω BIPOLAR : - Maximum output power CUT : 120 W - 150 Ω - Working frequency Monopolar / Bipolar : 380 kHz / 525 kHz - Selectable input voltage : 115- 230 VAC / 50 - 60 Hz - Maximum output power cut- coag BLEND : 100 W - 150 Ω - Maximum output power cut- coag CUT 80% : 100 W - 150 Ω - Maximum output power cut- coag CUT 60% : 100 W - 150 Ω - Maximum output power cut- coag CUT 40% : 60 W - 150 Ω - Maximum output power coag COAG : 120 W - 50 Ω - Vessel Sealing Feature : 200 W - 50 Ω Accessories : Electrode Handle Disposable : 5 pcs Electrode Handle Reusable : 1 pcs Bipolar Forceps : 1 pcs Bipolar Forceps Cable : 1 pcs Patient Plate, Disposable : 5 pcs Patient Plate, Cable Reusable : 1 pcs Electrode Blade : 6 pcs Electrode Needle : 3 pcs Electrode Ball : 3 pcs Foot Pedal, Double : 2 pcs Electrode Cleaning Sponge : 1 pcs	Uzumcu	EK - 410	Turkey - Europe