

SPESIFIKASI EK-160

NO	PRODUK	SPESIFIKASI	MERK	TYPE	NEGARA ASAL
1	Electrosurgical Unit	Features :	Uzumcu	EK - 160	Turkey - Europe
	160 Watt	- Five functions, Pure CUT, Cut-Coagulation BLEND, Superficial Coagulation			
		PROCED COAG, Deep Coagulation in absence of necrosis SOFT COAG and			
		BIPOLAR coagulation (with adapter).			
		- Absolute reliability of working conditions by microcontroller			
		- Digital Display for Delivered Power			
		- User Friendly menu			
		- Safety control of patient / plate contact using split neutral electrode			
		- Hand switch or foot switch activation			
		Specification :			
		- Maximum output power CUT : 160 W - 250 Ω			
		- Working frequency Monopolar / Bipolar : 600 kHz			
		- Selectable input voltage : 115- 230 VAC			
		- Maximum output power BLEND : 120 W - 200 Ω			
		- Maximum output power FORCED COAG : 100 W - 150 Ω			
		- Maximum output power SOFT COAG : 80 W - 100 Ω			
		- Maximum output power BIPOLAR : 60 W - 100 Ω			
		- Mains Frequency : 50 - 60 Hz			
		Accessories :			
		- Electrode Handle Disposable : 1 pcs			
		- Electrode Handle Reusable : 1 pcs			
		- Patient Plate, Reusable : 1 pcs			
		- Patient Plate, Cable Reusable : 1 pcs			
		- Electrode Blade : 2 pcs			
		- Electrode Needle : 1 pcs			
		- Electrode Ball : 2 pcs			
		- Foot Pedal, Single : 1 pcs			