

SPESIFIKASI Soled 15

NO	PRODUK	SPESIFIKASI	MERK	TYPE	NEGARA ASAL																																						
1	ACEM Surgical Lamp Trolley Mounted - ACEM SOLED 15	<p>Features :</p> <ul style="list-style-type: none"> - LED Illumination, High Brightnes - Lifting and mobile function , Brightnes adjustable, wide range voltage, matched with a handle - Power Supply with AC - LED examination light for diagnostics, minor surgery and universal applications. - It can be used for intensive care, recovery room, first aid, cosmetic surgery and dental sector - Contains all the advantages of LED technology and is suitable for multi-purpose uses thanks to its flexibility. It assures <ul style="list-style-type: none"> • excellent light intensity • IR-free light beam • long life • low power consumption - The high technological level combined with the use of high-powered LEDs - Very linear yield and a negligible performance decay for its entire life duration - The LEDs layout gives a visual comfort and produces a uniform, homogeneous and shadowless light - A round shape that makes it handy and functional both in use and move. - Its easy-to-move structure is suitable for diagnostics, test labs and dental surgery and its easy-to-grip. - Provided with an I-Sense touch panel to control all the functions of the lamp: <ul style="list-style-type: none"> • ON/OFF • Light intensity adjustment • Parts selection (SEL) • Brightness increase (Boost) - Boost” function or “brightness increase” is used to obtain a maximum light intensity in case of a wide light field. This approximate 20% increase deactivates automatically after 5 minutes <p>Thecnical Specification :</p> <table border="0" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 60%;">Product Class (EN 60601-2-41)</td> <td style="width: 40%;">: I</td> </tr> <tr> <td>Power supply</td> <td>: 100 – 240 VAC - 50/60 Hz</td> </tr> <tr> <td>DC voltage</td> <td>: 24 VDC</td> </tr> <tr> <td>Power consumption</td> <td>: 24 W</td> </tr> <tr> <td>Light source</td> <td>: LEDs</td> </tr> <tr> <td>Average life</td> <td>: 50.000 hrs about</td> </tr> <tr> <td>Lighting at the centre, Ec @ 100 cm</td> <td>: 65.000 Lux (85.000 Lux with Boost function)</td> </tr> <tr> <td>Light adjustment</td> <td>: 0% - 100%</td> </tr> <tr> <td>Lighting area surface 63 cm</td> <td>: 63 cm</td> </tr> <tr> <td>Colour temperature, CCT</td> <td>: 4.500 °K</td> </tr> <tr> <td>Colour rendering index, Ra</td> <td>: 95</td> </tr> <tr> <td>Light field dimension d50@ 100 cm</td> <td>: 12 cm</td> </tr> <tr> <td>Light field dimension d10@ 100 cm</td> <td>: 23 cm</td> </tr> <tr> <td>Focusable working distance</td> <td>: 70-150 cm</td> </tr> <tr> <td>Lighting depth L1+L2 98</td> <td>: 98 cm (with 60%) 125 cm (with 20 %)</td> </tr> <tr> <td>Light head weight</td> <td>: 2,1 Kg</td> </tr> <tr> <td>Light head diameter</td> <td>: 24 cm</td> </tr> <tr> <td>Handle Removable and sterilizable</td> <td>: Removable and sterilizable</td> </tr> <tr> <td>Colour</td> <td>: White RAL 9002</td> </tr> </table>	Product Class (EN 60601-2-41)	: I	Power supply	: 100 – 240 VAC - 50/60 Hz	DC voltage	: 24 VDC	Power consumption	: 24 W	Light source	: LEDs	Average life	: 50.000 hrs about	Lighting at the centre, Ec @ 100 cm	: 65.000 Lux (85.000 Lux with Boost function)	Light adjustment	: 0% - 100%	Lighting area surface 63 cm	: 63 cm	Colour temperature, CCT	: 4.500 °K	Colour rendering index, Ra	: 95	Light field dimension d50@ 100 cm	: 12 cm	Light field dimension d10@ 100 cm	: 23 cm	Focusable working distance	: 70-150 cm	Lighting depth L1+L2 98	: 98 cm (with 60%) 125 cm (with 20 %)	Light head weight	: 2,1 Kg	Light head diameter	: 24 cm	Handle Removable and sterilizable	: Removable and sterilizable	Colour	: White RAL 9002	Acem	Soled 15	Italy
Product Class (EN 60601-2-41)	: I																																										
Power supply	: 100 – 240 VAC - 50/60 Hz																																										
DC voltage	: 24 VDC																																										
Power consumption	: 24 W																																										
Light source	: LEDs																																										
Average life	: 50.000 hrs about																																										
Lighting at the centre, Ec @ 100 cm	: 65.000 Lux (85.000 Lux with Boost function)																																										
Light adjustment	: 0% - 100%																																										
Lighting area surface 63 cm	: 63 cm																																										
Colour temperature, CCT	: 4.500 °K																																										
Colour rendering index, Ra	: 95																																										
Light field dimension d50@ 100 cm	: 12 cm																																										
Light field dimension d10@ 100 cm	: 23 cm																																										
Focusable working distance	: 70-150 cm																																										
Lighting depth L1+L2 98	: 98 cm (with 60%) 125 cm (with 20 %)																																										
Light head weight	: 2,1 Kg																																										
Light head diameter	: 24 cm																																										
Handle Removable and sterilizable	: Removable and sterilizable																																										
Colour	: White RAL 9002																																										